

Step 4: Position the door assembly into the unit with the door latches on the top so that it fits squarely into the bottom of the hutch. Attach the bottom of the door unit by inserting four 1 1/4" screws into the predrilled holes in the bottom cleat. **Photo 5** Open the doors and attach the top of the door unit with four 1 1/4" screws inserted into the predrilled holes in the top cleat. **Photo 6** Next attach the sides of the door unit by inserting three 1 1/4" screws per side into the predrilled holes of the side cleats. **Photo 7**



Photo 5



Photo 6



Photo 7

Step 5: Attach the door knobs by inserting the pan head screws in through the inside of the predrilled holes in the door fronts and into each knob and tighten. **Photo 8** Turn the unit over to attach the back panels. Lay the first panel so that the beaded side faces the front of the unit and the ship lap is in the center of the unit. Lay the second back panel the same way so that the ship lap sides of each panel fit together. The top of each panel should be flush with the top of the unit. Attach with 8 nails per long side and 4 nails per top and bottom. **Photo 9**



Photo 8



Photo 9

Step 6: Stand the unit upright and position the shelf clips for the shelves. The smaller shelf 10 1/2"W goes inside the door unit.

**For questions or ordering information contact The Maine Bucket Company's
customer service at 1-800-231-7072
www.mainebucket.com**